



## SPECIFICATION DATA SHEET

Casita Laminates combines durability with a refined aesthetic, offering a cost effective flooring solution with a premium look.

Available in a range of contemporary colours, this range provides flexibility for various interior designs. With an abrasion resistance rating of AC4, this laminate is suitable for all residential spaces, including high traffic areas such as entryways, kitchens, living rooms, and playrooms.

The surface is low maintenance and easy to clean, making it a practical option for everyday use in busy households.

### Product Details

<b>Board Style</b>	Plank
<b>Board Thickness</b>	12 mm
<b>Board Size</b>	1215 x 195 mm
<b>Edge Profile</b>	Micro Bevelled
<b>Locking System</b>	Uniclic
<b>Installation Method</b>	Floating only
<b>Sqm/ Box</b>	1.896 m <sup>2</sup>
<b>Pieces / Box</b>	8
<b>Box / Pallet</b>	50
<b>Weight / Box</b>	20 kg
<b>Suitable Application</b>	Residential & Light Commercial

### Performance & Safety Testing

<b>Slip (AS 4586-2013)</b>	P3 (SRV 40)
<b>Fire (AS ISO 9239.1-2003)</b>	8.6 kW/m <sup>2</sup>
<b>Acoustic Outcome</b>	L'nTw 40 (2 mm Green underlay)
<b>AAAC Rating</b>	6 Star

Reports are available upon request.



Images are for general illustration only. Actual product colours may differ due to variations in screen displays or printing processes. The scale of the images does not reflect true colour variation. For an accurate representation, please refer to physical samples. Images are not legally binding.

## Technical Summary

<b>Abrasion Rating</b>	AC4
<b>Surface Finish</b>	RealFeel Texture Matte
<b>Protective Overlay</b>	Aluminium Oxide Film
<b>Decorative Layer</b>	HD Natural Wood Grain
<b>Pattern Repeats</b>	7-12 Patterns
<b>Core Structure</b>	High Density Fibreboard
<b>Backing Layer</b>	Moisture Resistant Melamine
<b>Thickness Swelling</b>	≤15 %
<b>Water Resistance</b>	Up to 8 hours
<b>Density</b>	850 kg/m <sup>3</sup>
<b>Formaldehyde Test</b>	Method: ASTM D6007-14
<b>Formaldehyde Result</b>	0.06 ppm (per million parts of air)
<b>Environmental</b>	Sourced from sustainable managed resources



This specification data sheet has been prepared by National Select Floors. All information provided was accurate at the time of writing and publication. National Select Floors reserves the right to alter product details at any time without prior notification. Images included are for illustrative purposes only and do not confer any rights or guarantees.

National Select Floors recommends installation by a professional flooring contractor or skilled tradesperson and must follow the Australian Standards for flooring installations. All installations must also be performed in accordance with National Select Floors installation guidelines. If you have any concerns regarding the installation process, please contact your reseller.

Installation guidelines and Warranty information are available from our website.